



## Technical Data Sheet

### LUBRICO MARINE 2T TC 2-STROKE ENGINE LUBRICANT FOR SNOWMOBILE

#### PRODUCT DESCRIPTION:

LUBRICO MARINE 2T TC represents a cutting-edge fully synthetic oil, meticulously crafted for 2-stroke engines in snowmobiles. This oil is meticulously formulated with precisely chosen esters, offering effective detergency and dispersancy characteristics. Its synthetic base fluids guarantee outstanding low-temperature fluidity while retaining exceptional lubricating capabilities even under high operating temperatures. Marine 2T TC is designed to safeguard and deliver peak performance under diverse operating conditions, establishing itself as a dependable option for snowmobile engines.

#### APPLICATION:

LUBRICO MARINE 2T TC is advised for application in 2-stroke engines equipped with injector systems or those requiring premix lubrication. Its versatility extends to both racing circuits and everyday driving scenarios that demand superior performance. Adhering to the fuel/oil mix ratio specified by the original equipment manufacturer (OEM) is crucial. In cases where the specific ratio is unspecified, it is generally recommended to utilize a 50:1 fuel/oil mix ratio.

#### FEATURES & BENEFITS:

- The low ash formulation helps prevent the accumulation of deposits on pistons and ports.
- Instantly blends with gasoline and maintains stability over time.
- Outstanding lubricating properties and cold-flow performance even in extreme temperatures.
- Decreases friction and wear, thereby extending the engine's lifespan.

#### PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- ISO L-EGD
- JASO FD

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	LUBRICO MARINE 2T TC
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	7.5
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	41.4
Viscosity Index	ASTM D2270	-	150
TBN	ASTM D2896	Mg KOH/g	2
FLASH POINT	ASTM D92	°C	152
POUR POINT	ASTM D97	°C	-45
SPECIFIC GRAVITY	ASTM D4052	g/cm3	TBR

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [lubrico.ae](http://lubrico.ae)